

4x4 Scissor Lifts Skyjack 6832RT & Haulotte compact 12DX

Unit 16, London Industrial Park,
Eastbury Road,
Beckton,
London
E6 6LP

Phone: 020 7511 2090



- Up to 10.14m platform height on H12DX model.
- Up to 565kg working platform load on H12DX model.
- Diesel powered, Rough Terrain 4x4 operation with self-levelling hydraulic jacks.

Specification

4x4 Scissor Lifts Skyjack 6832RT & Haulotte compact 12DX

Unit 16, London Industrial Park,
Eastbury Road, Beckton, London E6 6LP

W www.londontowerservice.co.uk

E info@londontowerservice.co.uk

F 020 7511 8060

P 020 7511 2090

Skyjack 6832RT Haulotte 12DX

Dimensional Data		
A. Platform Height – Elevated	9.75m (32ft. 0in.)	10.14m (33ft. 3in.)
B. Platform Height – Lowered	1.37m (4ft. 5in.)	1.23m (4ft. 0.5in.)
C. Stowed Height (Guardrail)	2.50m (8ft. 3in.)	2.54m (8ft. 4in.)
Stowed Height (Rails Folded)	1.75m (5ft. 9in.)	1.40m (4ft. 6in.)
D. Platform Dimensions	1.43m x 2.44m (4ft. 8in. x 8ft. 2in.)	1.54m x 2.50m (5ft. 1in. x 8ft. 2in.)
Platform Extension	1.50m (5ft. 0in.)	1.20m (3ft. 11in.)
E. Overall Machine Width	1.73m (5ft. 8in.)	1.80m (6ft. 0in.)
F. Overall Machine Length	2.70m (8ft. 11in.)	2.65m (8ft. 7in.)
G. Wheelbase	2.05m (6ft. 8.5in.)	1.87m (6ft. 1in.)
H. Ground Clearance	0.20m (8in.)	0.25m (10in.)
Tyre Size, foam filled	0.66m x 0.21m (26in. x 12in.)	0.66m x 0.21m (26in. x 12in.)
Performance Data		
Max. Platform Capacity	454kg (1,000lbs.)	565kg (1,245lbs.)
Lift/Lower Time	41/40 seconds	40/45 seconds
Maximum Drive Height	9.75m (32ft. 0in.)	10.14m (33ft. 3in.)
Drive Speed, Lowered	7.0km/h (4.5mph)	5.5km/h (3.4mph)
Drive Speed, Elevated	0.8km/h (0.5mph)	0.8km/h (0.5mph)
Gradeability	40%	40%
Turning Radius (Inside)	1.93m (6ft. 4in.)	1.21m (4ft. 0in.)
Turning Radius (Outside)	4.17m (13ft. 8in.)	3.73m (12ft. 3in.)
Power System/Chassis		
Engine	Diesel	Diesel
Brakes	Hydraulic	Hydraulic
Gross Vehicle Weight	3,475kg (7,660lbs.)	3,830kg (8,443lbs.)
Rail Type	Fold Down	Fold Down

