

Electric Scissor Lift M4069 4x4

Unit 16, London Industrial Park,
Eastbury Road,
Beckton,
London
E6 6LP

Phone: 020 7511 2090



- Up to 12.19m (40 ft.) platform height.
- Up to 800kg working platform load.
- Automatic, quick charging generator system.
- All wheel drive, foam filled non-marking tyres with traction control system.

Specification

Electric Scissor Lift M4069 4x4

Unit 16, London Industrial Park,
Eastbury Road, Beckton, London E6 6LP

W www.londontowerservice.co.uk

E info@londontowerservice.co.uk

F 020 7511 8060

P 020 7511 2090

Dimensional Data

A. Platform Height – Elevated	12.19m	40ft. 0in.
B. Platform Height – Lowered	1.75m	5ft. 9in.
C. Platform Railing Height	1.10m	3ft. 7.5in.
Overall Height	2.81m	9ft. 2.5in.
D. Stowed Height (Rails Folded)	2.0m	6ft. 7in.
E. Platform Dimensions	1.65m x 2.92m	6ft. 5in. x 9ft. 7in.
F. Platform Extension	0.91m	3ft. 0in.
G. Overall Machine Width	1.75m	5ft. 9in.
H. Overall Machine Length	3.10m	10ft. 2in.
I. Wheelbase	2.30m	7ft. 6.5in.
J. Ground Clearance	0.20m	8in.
Tyre Size, (Foam Filled, Non-Marking)	240/55-17.5	

Performance Data

Max. Platform Capacity	362kg	800lbs.
– Capacity On Deck Extension	113kg	250lbs.
Lift/Lower Time	54/50 seconds	
Maximum Drive Height	9.14m	30ft. 0in.
Drive Speed, Lowered	4.8km/h	3mph
Drive Speed, Elevated	0.64km/h	0.4mph
Gradeability	45%	
Turning Radius (Inside)	2.29m	7ft. 6in.
Turning Radius (Outside)	4.72m	15ft. 6in.

Power System/Chassis

Batteries	8 x 6V, 370 amp-hr	
Charger	21 Amp Automatic	
Generator Set	Fully Automatic, 45 Amp Kubota 6hp Air-Cooled Engine	
Pump	Electric, Series Wound	
Hydraulic Reservoir	32.18L	8.5gal.
Brakes (On Drive Wheels)	Spring Applied Hydraulically Released Discs	
Gross Vehicle Weight	4,790kg	10,560lbs.
Rail Type	Fold Down	
Drive	2 x 5.5hp Shunt Wound	

