

Hire Equipment

Electric Scissor Lifts (Narrow) 1930ES & 2630ES

Unit 16, London Industrial Park,
Eastbury Road,
Beckton,
London
E6 6LP

Phone: 020 7511 2090



- Up to 7.75m platform height on 2630ES model.
- Up to 230kg working platform load.
- Security coded operation to help prevent unauthorised use on site.

Electric Scissor Lifts (Narrow) 1930ES & 2630ES

Unit 16, London Industrial Park,
Eastbury Road, Beckton, London E6 6LP

W www.londontowerservice.co.uk

E info@londontowerservice.co.uk

F 020 7511 8060

P 020 7511 2090

| | Model 1930ES | Model 2630ES |
|---------------------------------|--|--|
| Dimensional Data | | |
| A. Platform Height – Elevated | 5.72m (18ft. 9in.) | 7.75m (25ft. 5in.) |
| B. Platform Height – Lowered | 0.86m (2ft. 10in.) | 1.23m (4ft. 0.5in.) |
| C. Platform Railing Height | 1.10m (3ft. 7.5in.) | 1.10m (3ft. 7.5in.) |
| Overall Height | 1.98m (6ft. 5in.) | 2.20m (7ft. 3in.) |
| D. Stowed Height (Rails Folded) | 1.62m (5ft. 4in.) | 1.94m (6ft. 4.5in.) |
| E. Platform Dimensions | 0.76m x 1.87m (2ft. 6in. x 6ft. 1.5in.) | 0.76m x 2.30m (2ft. 6in. x 7ft. 6.5in.) |
| F. Platform Extension | 0.90m (2ft. 11.5in.) | 0.90m (2ft. 11.5in.) |
| G. Overall Machine Width | 0.76m (30in.) | 0.76m (30in.) |
| H. Overall Machine Length | 1.87m (6ft. 1.5in.) | 2.30m (7ft. 6.5in.) |
| I. Wheelbase | 1.60m (5ft. 3in.) | 1.88m (6ft. 2in.) |
| J. Ground Clearance | 0.09m (3.5in.) | 0.09m (3.5in.) |
| Tyre Size, (Non-Marking Solid) | 0.31m x 0.10m (12.5in. x 4in.) | 0.40m x 0.12m (16in. x 5in.) |
| Performance Data | | |
| Max. Platform Capacity | 230kg (500lbs.) | 230kg (500lbs.) |
| – Capacity On Deck Extension | 120kg (250lbs.) | 120kg (250lbs.) |
| Lift/Lower Time | 22/28 seconds | 40/40 seconds |
| Maximum Drive Height | 5.72m (18ft. 9in.) | 7.75m (25ft. 5in.) |
| Drive Speed, Lowered | 4.8km/h (3.0mph) | 4.4km/h (2.75mph) |
| Drive Speed, Elevated | 0.8km/h (0.5mph) | 0.8km/h (0.5mph) |
| Gradeability | 25% | 25% |
| Turning Radius (Inside) | 0 | 0 |
| Turning Radius (Outside) | 1.75m (5ft. 9in.) | 2.06m (6ft. 9in.) |
| Power System/Chassis | | |
| Batteries | 4 x 6V, 220 amp-hr | 4 x 6V, 220 amp-hr† |
| Charger | 20 Amp Automatic (120V/240V– 50/60HZ) | 20 Amp Automatic (120V/240V– 50/60HZ) |
| Pump | Fixed Clearance Gear | Fixed Clearance Gear |
| Hydraulic Reservoir | 3.6L (0.95gal.) | 4.73L (1.25gal.) |
| Brakes (On Drive Wheels) | Electric, Auto Friction | Electric, Auto Friction |
| Gross Vehicle Weight | 1,565kg (3,450lbs.) | 2,155kg (4,750lbs.) |
| Rail Type | Fold Down | Fold Down |
| Drive | 6kW (8hp) | 6kW (8hp) |

