

Self Propelled Access Platform HR15/HR17

Unit 16, London Industrial Park,
Eastbury Road,
Beckton,
London
E6 6LP

Phone: 020 7511 2090



- Up to 17.20m working height on HR17 & 15.20m on HR15.
- Up to 9.60m outreach.
- Dual fuel, battery or diesel operated (diesel only on HR17).

Specification

Self Propelled Access Platform HR15/HR17

Unit 16, London Industrial Park,
Eastbury Road, Beckton, London E6 6LP

W www.londontowerservice.co.uk


E info@londontowerservice.co.uk

F 020 7511 8060

P 020 7511 2090

	HR15N	HR17 4x4
Dimensional Data		
Height - Working	15.60m (51ft. 0in.)	17.20 (56ft. 6in.)
Height - Platform	13.60m (44ft. 7in.)	15.20m (49ft. 10in.)
Outreach - Working	9.60m (31ft. 6in.)	9.60m (31ft. 6in.)
Slew	360 degrees	360 degrees
Flyboom Arc	150 degrees	150 degrees
A. Width	1.50m (4ft. 11in.)	2.00m (6ft. 7in.)
B. Height - Stowed	1.95m (6ft. 6in.)	2.10m (6ft. 11in.)
C. Length - Stowed	4.69m (15ft. 5in.)	4.70m (15ft. 5in.)
D. Length - Overall	5.94m (19ft. 6in.)	6.00m (19ft. 8in.)
Performance Data		
Turning Radius - Inside	1.21m (3ft. 11in.)	1.75m (5ft. 9in.)
Turning Radius - Outside	3.31m (10ft. 10in.)	4.22m (13ft. 10in.)
Platform Capacity	225kg (500lbs.)	225kg (500lbs.)
Platform Size	1.50m x 0.70m (4ft. 11in. x 2ft. 4in.)	1.80m x 0.70m (5ft. 11in. x 2ft. 4in.)
Drive Speed	4km/h (2.5mph)	6.6km/h (4.1mph)
Gradeability	25%	45%
Power System/Chassis		
Control System	Fully proportional hydraulic	Fully proportional hydraulic
Power	Bi-energy (Diesel engine and Battery)	Diesel engine
Weight	6,400kg (14,097lbs.)	6,140kg (13,508lbs.)

HR15N -1 0 1 2 3 4 5 6 7 8 9 10



HR17 4x4 0 1 2 3 4 5 6 7 8 9 10

